

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

Delphion

RESEARCH

INTEGRATED IAM

SERVICES


INSIDE DELPHION

[Log Out](#) | [Work Files](#) | [Saved Searches](#)[My Account](#) | [Products](#) | [News](#) | [Events](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#)[Help](#)


## The Delphion Integrated View

Buy Now:  PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#)  GoView: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#) [Email this to a friend](#)Title: **JP8031419A2: NEGATIVE ELECTRODE MATERIAL FOR LITHIUM SECONDARY BATTERY AND LITHIUM SECONDARY BATTERY**Country: **JP Japan**Kind: **A**Inventor: **MATSUYOSHI HIROAKI;  
NAKAGAWA YOSHITERU;**Assignee: **OSAKA GAS CO LTD**  
[News, Profiles, Stocks and More about this company](#)Published / Filed: **Feb. 2, 1996 / July 14, 1994**Application Number: **JP1994000162417**IPC Code: **H01M 4/58; H01M 4/02; H01M 10/36;**Priority Number: **July 14, 1994 JP1994000162417**Abstract: **Purpose:** To obtain the lithium secondary battery, which has excellent energy density, excellent discharging characteristic and excellent cycle characteristic, by using carbide, which is obtained by baking Brooks-Taylor type mesophase small spherical body, as the negative electrode material.**Constitution:** Brooks Taylor type mesophase small spherical body is baked in the nitride atmosphere so as to obtain the Brooks-Taylor type mesophase small spherical body carbide at 1.50-2.00 of true specific gravity. It is used for the structural member of a negative electrode of a lithium secondary battery. Raw material of MCMB (meso carbon micro beads) of the Brooks-Taylor type mesophase is manufactured from coal tar or pitch. Spherical body of type MCMB has the structure that condensed multi-ring aromatic molecular are vertically laminated in the optical axis direction. Consequently, since the end surface of carbon is arranged vertical to the surface of the spherical body of MCMB, lithium ion can easily go in and out at the time of charge and discharge, and the diffusing speed thereof is considered high.

COPYRIGHT: (C)1996,JPO

Family: [Show 3 known family members](#)Other Abstract Info: **CHEMABS 124(18)237246B CAN124(18)237246B DERABS C96-144165  
DERC96-144165**[View Image](#)

1 page

[Nominate](#)[this for the Gallery...](#)